

### Description

SMA connectors are precision connectors for microwave applications up to 18 GHz. The extended frequency version operates with excellent return loss performances up to 26.5 GHz. There is a huge variety of applications for SMA connectors, as in telecom, test & measurement, instruments, avionics, etc.

### 11521232 -- RF CONNECTOR - 50OHMS , SMA FEMALE , STRAIGHT , BULKHEAD REAR MOUNT , SOLDER TYPE , RG178 CABLE

**PART CODE: 11521232**

|                           |                     |
|---------------------------|---------------------|
| Type                      | RF Connector        |
| Gender                    | Jack (Female)       |
| Orientation               | Straight            |
| Termination Style         | Cable – Solder      |
| Impedance (Ohms)          | 50                  |
| Body Finish               | Gold                |
| Body Material             | Brass               |
| Contact Finish            | Gold                |
| Contact Material          | Brass               |
| Contact Termination Style | Solder              |
| Insulator Material        | PTFE                |
| Cable Type                | RG178               |
| Coupling Mechanism        | Threaded            |
| Mounting Feature          | Bulkhead Rear Mount |
| Max Frequency (GHz)       | 18                  |
| Polarity                  | Standard            |
| Thread Direction          | Standard            |
| Min. Temp. (Celsius)      | -65                 |
| Max. Temp. (Celsius)      | 165                 |



### VINSURWAVES

**Address:** C-211, First Block, KSSIDC Complex, Near Software Technology Park of India, Electronics City Phase-1, Bengaluru - 560100, Karnataka, INDIA, Phone: 080-28520115, Mob: +91- 9886991616, E-mail: info@vinsurwaves.com | Website: www.vinsurwaves.com.