

Description

SMA connectors are precision connectors for microwave applications up to 18 GHz. The extended frequency version operates with excellent return loss performances up to 26.5 GHz. There is a huge variety of applications for SMA connectors, as in telecom, test & measurement, instruments, avionics, etc.

11921232 -- RF CONNECTOR - 50OHMS , RP SMA FEMALE , STRAIGHT , BULKHEAD REAR MOUNT , SOLDER TYPE , RG178 CABLE

PART CODE: 11921232

Type	RF Connector
Gender	Jack (Female)
Orientation	Straight
Termination Style	Cable – Solder
Impedance (Ohms)	50
Body Finish	Gold
Body Material	Brass
Contact Finish	Gold
Contact Material	Brass
Contact Termination Style	Solder
Insulator Material	PTFE
Cable Type	RG178
Coupling Mechanism	Threaded
Mounting Feature	Bulkhead Rear Mount
Max Frequency (GHz)	18
Polarity	Reverse
Thread Direction	Standard
Min. Temp. (Celsius)	-65
Max. Temp. (Celsius)	165



VINSURWAVES

Address: C-211, First Block, KSSIDC Complex, Near Software Technology Park of India, Electronics City Phase-1, Bengaluru - 560100, Karnataka, INDIA, Phone: 080-28520115, Mob: +91- 9886991616, E-mail: info@vinsurwaves.com | Website: www.vinsurwaves.com.