

Description

SMB (Sub Miniature version B) connectors are coaxial RF Connectors. The SMB interface features a snap-on coupling mechanism and is available in 50 Ohm and 75 Ohm configurations. SMB connectors conform to the requirements of MIL-C-39012, and the interface is in compliance with MIL-STD-348. SMB connectors offer broadband performance with low reflection DC to 4 GHz and utilize die cast components on non-critical areas to provide a low-cost solution.

11621370 -- RF CONNECTOR - 50OHMS , SMB FEMALE , STRAIGHT , 2 HOLE FLANGE , ROUND POST

PART CODE: 11621370

Type	RF Connector
Gender	Jack (Female)
Orientation	Straight
Termination Style	Round Post
Impedance (Ohms)	50
Body Finish	Gold
Body Material	Brass
Contact Finish	Gold
Contact Material	Brass
Contact Termination Style	Solder
Insulator Material	PTFE
Coupling Mechanism	Push-on
Mounting Feature	2 Hole Flange
Max Frequency (GHz)	4
Polarity	Standard
Extended Dielectric	Yes
Extended Dielectric Length (mm)	
Min. Temp. (Celsius)	-65
Max. Temp. (Celsius)	165



VINSURWAVES

Address: C-211, First Block, KSSIDC Complex, Near Software Technology Park of India, Electronics City Phase-1, Bengaluru - 560100, Karnataka, INDIA, Phone: 080-28520115, Mob: +91- 9886991616, E-mail: info@vinsurwaves.com | Website: www.vinsurwaves.com.