

Description

SMB (Sub Miniature version B) connectors are coaxial RF Connectors. The SMB interface features a snap-on coupling mechanism and is available in 50 Ohm and 75 Ohm configurations. SMB connectors conform to the requirements of MIL-C-39012, and the interface is in compliance with MIL-STD-348. SMB connectors offer broadband performance with low reflection DC to 4 GHz and utilize die cast components on non-critical areas to provide a low-cost solution

11622214 -- RF CONNECTOR - 50OHMS , SMB FEMALE , RIGHT ANGLE , BULKHEAD REAR MOUNT , CRIMP TYPE , RG316 , RG174 , RG188 , LMR100 CABLE

PART CODE: 11622214

| | |
|---------------------------|---------------------|
| Type | RF Connector |
| Gender | Jack (Female) |
| Orientation | Right Angle |
| Termination Style | Cable – Crimp |
| Impedance (Ohms) | 50 |
| Body Finish | Gold |
| Body Material | Brass |
| Contact Finish | Gold |
| Contact Material | Brass |
| Contact Termination Style | Solder |
| Insulator Material | PTFE |
| Cable Type | RG316 |
| Coupling Mechanism | Push-on |
| Mounting Feature | Bulkhead Rear Mount |
| Max Frequency (GHz) | 4 |
| Polarity | Standard |
| Thread Direction | Standard |
| Min. Temp. (Celsius) | -65 |
| Max. Temp. (Celsius) | 165 |



VINSURWAVES

Address: C-211, First Block, KSSIDC Complex, Near Software Technology Park of India, Electronics City Phase-1, Bengaluru - 560100, Karnataka, INDIA, Phone: 080-28520115, Mob: +91- 9886991616, E-mail: info@vinsurwaves.com | Website: www.vinsurwaves.com.